

ON-30

Power by WEICHAI

WP2.3D33E200

Prime power: 24KW/30KVA

Standby power: 26.4KW/33KVA

GENERATING POWER SOLUTIONS

Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs




The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.
Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.



DIMENSION			OPEN TYPE	SILENT TYPE
	Length (L)	mm	1650	2100
	Width (W)	mm	650	860
	Height (H)	mm	1030	1100
	Dry weight	kg	642	763
	Fuel tank	L	100	80

ONEWPOWER

WWW.ONEWPOWER.COM

Technical Data

Model ON-30

Rated prime power	KW	24
Rated standard power	KW	26.4
Rated voltage line to line	V	380~415
Maximun sound level	dB(@7m)	≤72

Engine

Model	WP2.3D33E200	
Aspiration	Turbocharged	
Fuel system	mechanical pump	
No. cylinders	4	
Displacement	Liquid	2.3
Bore*Stroke	mm	89*92
Compression ratio	17.5:1	
Rated speed	r/min	1500
Rated net power(with fan)	Kw	26
Governor type	Electronic	

Exhaust system

Exhaust gas flow	144kg/h
Exhaust gas temp	° F (° C) <650
Max back pressure	8KPA

Aspiration system

Max inlet pressure	kPa	≤3.5
Combustion volume	L/s	/
Air flow	kg/h	138

Fuel system

100% load(Prime power)	L/h	7.7
75% load(Prime power)	L/h	5.6
50% load(Prime power)	L/h	3.9
Fuel tank capacity	L	80

Lubrication system

Oil capacity	L	8
Oil consumption	g/kwh	28.3
Oil pressure	kPa	10
(continuous operation)		

Cooling system

Coolant capacity	L	5
Thermostat operation range	°C	76-88
Max water temperature	°C	98

Alternator

Model	ON-30	
Phase	3	
Voltage	V	380~415
Bearing	1	
Power factor	0.8	
Frequency	Hz	50
Prime power	KW	24
Exciter Type	Brushless, self-exci	
Voltage regulation	%	±0.5
Protection Grade	IP 23	
Insulation grade	H/H	
Altitude	m	≤1000

Controller

Model	
Protective functions:	
■ Low oil pressure	
■ High water temperature	
■ High/low voltage	
■ High Engine Temperature and Overspeed.	
■ Voltage regulator frequency regulator	
■ Emergency stop	
■ Start failure	



Control Module Options



- Auto generator control module
- Control module with "Three Remote Control" functions
- ATS auto load transfer screen
- Synchronising control modules
- Power output cabinet

Standard features

- Engine
- Radiator 50°C max, fans are driven by belt
- 24V charge alternator
- Alternator: single bearing alternator IP23, insulation class H/H
- Standard auto control system
- One set of air filter, fuel filter, oil filter
- Main line circuit breaker/MCCB
- Base fuel tank
- Two 24V batteries, rac and cable
- Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler)
- User manual

Options

- Battery charge
 - Engine heater
 - Alternator heater
 - PMG
 - Water oil separator
 - Daily fuel tank
 - Remote control panel
 - Automatic transfer switch/ATS
 - Switch box
- Standard: ● Options: ○

Warranty



WEICHAH ENGINE

12 months from date of purchase and 1000 hours.

Generator

12 months from date of purchase or 1000 hours (whichever occurs first).

Dimensions



ONEWPOWER

ADD: NO . 1 0 7 XIYUAN ROAD , JINAN DISTRICT,
FUZHOU CITY, FUJIAN, CHINA
Phone: 15980204507 E-mail: jina@onewpower.com
WWW.ONEWPOWER.COM

